

CL21B 为无感结构，用金属化聚酯膜卷绕而成，导线采用镀锡铜包钢线，塑壳封装。
CL21B is a non-inductive structure, wound with metallized polyester film, and the wires are made of tinned copper clad steel wire and encapsulated in a plastic case

特 点 FEATURES

- 体积很小，有良好自愈性；有脉冲强度，高可靠性,外观一致性好
Small in size, with good self-healing properties; Pulse strength, high reliability, and good appearance consistency

用 途 APPLICATIONS


- 适用于直流和旁路、耦合 适用于滤波、低脉冲电路
Suitable for DC and bypass, coupled for filtering, low pulse circuits

技 术 要 求 SPECIFICATIONS

- 引用标准 Reference Standard: GB 7332 (IEC60384-2)
- 气候类别 Climatic Category: 55/105/21
- 额定电压 Rated Voltage: 100VDC~1000VDC
- 电容量范围 Capacitance Range: 0.1~10.0μF
- 电容量偏差 Capacitance Tolerance: ±5%(J),±10%(K),±20%(M)
- 耐电压 Voltage Proof: 1.6UR(5s)
- 损耗角正切 Dissipation Factor: ≤1.0%(20℃,1KHZ)
- 绝缘电阻 Insulation Resistance: C≤0.3μF: R≥15000MΩ
C>0.33μF: RC≥5000MΩ·μF

产 品 尺 寸 DIMENSIONS

额定电 压 V-	标称容 量 uF	外形尺寸(mm)				
		L ±1.0	H ±1.0	T ±1.0	d ±0.5	P ±0.5
63	0.01	7.2	6.5	2.5	0.5	5.0
63	0.1	7.2	6.5	2.5	0.5	5.0
63	0.22	7.2	7.5	3.5	0.5	5.0
100	4.7	18.0	14.5	8.5	0.8	15.0
630	0.0068	7.2	7.5	3.5	0.5	5.0



具体尺寸和技术参数，可按客户要求协商确定。Special requirements can be designed at the request of customers.