MEIYANG



CL21XB 为无感结构,用金属化聚酯膜卷绕而成,导线采用镀锡铜包钢线,使用塑壳封装 CL21XB is a non-inductive structure, wound with metallized polyester film, and the wire is made of tinned copper clad steel wire, packaged in a plastic case

特 点 FEATURES

□ 塑壳封装, 阻燃性好

Plastic shell packaging with good flame retardancy

□ 容量范围宽,体积小

Wide capacitance rang, small size

□ 自愈性好,寿命长

Long life due to self-healing effect

用 途 APPLICATIONS

□ 适用于直流和 VHF 级信号的隔直流、旁路和偶合 Suitable for blocking, by-pass and coupling of DC and signals to VHF range

□ 广泛用于滤波、低脉动电路
Widely used in filter and low pulse circuits

技 术 要 求 SPECIFICATIONS

□ 引用标准 Reference Standard: GB 7332 (IEC 60384-2)

□ 气候类别 Climatic Category: 55/105/21

□ 额定电压 Rated Voltage: 50/63VDC,100VDC

□ 电容量范围 Capacitance Range: 0.001~1.0µF

□ 电容量偏差 Capacitance Tolerance: ±5%(J),±10%(K),±20%(M)

□ 耐电压 Voltage Proof: 1.6UR(5s)


□ 损耗角正切 Dissipation Factor: ≤1%(20°C,1KHZ)

产品尺寸

DIMENSIONS

标称 容量 μF	50/63VDC 100VDC				
	外形尺寸(mm) Dimensions				
	w	Н	Т	P ±1.0	d ±0.05
0.01	7.2	6.5	2.5	5.0	0.5
0.1	7.2	6.5	2.5	5.0	0.5





具体尺寸和技术参数,可按客户要求协商确定。Special requirements can be designed at the request of customers.